www.buyersproducts.com
Phone (440) 974-8888
Fax 800-841-8003

Installation Instructions

3/4" Marker Lights
5627518, 5627519, 5627528, 5627529

- 3/4" Small light head for installation in tailgates, truck box lids, or the side of the vehicle.
- Multi-function combination warning light with side marker front viewing position.
- Aluminum base for efficient heat dissipation and maximum durability

1. Technical Specifications

Amps/Volts:	0.6A@12VDC, 0.3A@24VDC
Voltage Range:	DC 10-30V
Color:	Single color
LED:	Warning: 5W x 1pcs and Position: 0.2W x 2pcs
Flash Pattern:	14 Flash Patterns
IP Rating:	IP67
Operating Temp.:	-30°C to +60°C
Mount:	Flush or Tube Mount
Certifications:	ECE R65 Class1(4 units), R10, R148, SAE J592 and J2043

2. Flash Patterns

1	Single 2HZ
2	Double 2HZ
3	Single SAE
4	Double SAE
5	Quad 2HZ
6	Quad SAE
7	Warp 1HZ

8	Single to Double 2HZ
9	Single to Quad 2HZ
10	Single to Double SAE
11	Single to Quad SAE
12	Single to Warp
13	Steady on 50%
14	Steady on 10%

3. Mounting hole Diameter: 3/4" or 19mm

WARRANTY

Buyers Products Co. warrants all truck/trailer hardware manufactured or distributed by it, to be free from defects in material and workmanship for a period of one year from date of shipment. Parts must be properly installed and used under normal conditions. Any product which has been altered, including modification, misuse, accident or lack of maintenance will not be considered under warranty. Normal wear is excluded. The sole responsibility of Buyers Products Co. under this warranty is limited to repairing or replacing any part or parts which are returned, prepaid, and are found to be defective by Buyers Products Co. Authorization from Buyers Products Co. must be obtained before returning any part. No charges for transportation or labor performed on Buyers' products will be allowed under this warranty.

4. Wiring Instruction

PRODUCT 1 **PRODUCT 2**

- **RED** — Warning light "+" 10-30 V DC — **RED**
- **BLACK** — GND "-" — **BLACK**
- **WHITE** – – – – – Alternate Flash – – – – – **WHITE**


With the power off, connect the **WHITE** wire form one light head to **RED** wire and leave the other unconnected. Their patterns will alternate when the light heads are activated

- **YELLOW** — Synchronization, Flash Patterns Selection and Reset — **YELLOW**

- Connect **YELLOW** wires of all lights together for
- Apply **YELLOW** wire to +VDC less than 1 second to next pattern
- Apply **YELLOW** wire to +VDC more than 5 seconds and release for reset the pattern.

- **GREEN** — Position Light — **GREEN**

When the red wire and the green wire are connected together then warning light function will take precedence over the position light



A 1A fuse is required for connecting the positive terminal of the product to the battery

5. Dimensions (in mm)

