


Installation Instructions

.....

8892010 - CAB MARKER STROBE REPLACEMENT KIT FOR 2015-2019 GMC/CHEVY TRUCKS



INSTALLATION INSTRUCTIONS:

For safety, disconnect power from the vehicles battery before proceeding.

1. Unscrew the two front sun visors and remove the sun visor support clips.
2. Unscrew the two front A pillar covers and remove. Pull down the top of the rubber door seal to reveal the edge of the headliner.
3. Pull down the front edge of the headliner inside the vehicle.
4. Unscrew the factory roof lights from the outside of the vehicle and remove the factory lights.
5. Install the LED flasher under the dash. Run the output wire harness up the A pillar.
6. Run each of the output wires through each hole on the roof, connecting each wire to each light.
7. Plug in each light to the factory plugs, install the lights, and tighten down.
8. Run the R/L wire harness up the A pillar.
9. Cut the factory power wire feeding the roof lights before the first light.

DO NOT CUT THE GROUND WIRE!

10. Connect R/L in to the side of the cut wire going down the A pillar.
11. Connect R/L out to the cut wire leading up to the lights.
12. Connect the black wire to a vehicle ground. Connect the red wire from the wire harness to a 12-volt fused switch or factory switch if equipped.
13. Connect the yellow wire to included momentary switch. Yellow wire does not need to be connected, during installation turn warning mode on and touch the yellow wire quickly to 12-volts to advance to the next flash pattern.
14. Once a flash pattern has been chosen, tape the end of the yellow wire to avoid accidental contact with power.
15. Replace truck interior pieces in reverse order of removal.



LED SPECIFICATION	
Input Power	5W / 24W
Operating Voltage	DC 12-14V
Lumens	2200lm for the set
IP Rate	IP68
LED Chip Model	5730
LED Quantity	24 LEDs + 153LEDs + 24 LEDs
Color	Amber
Main Material	PC +UV
Operating Life	> 30000 hrs
Operating Temperature	-40°F ~ +185°F

FLASHER SPECIFICATION	
Input Power	90W
Operating Voltage	DC 12-14V
IP Rate	IP68
Main Material	Aluminum 6063
Operating Life	> 30000 hrs
Operating Temperature	-40°F ~ +185°F

AFTER SALE SERVICE			
Purchase Date	Year:	Month:	Date:
Warranty period	2 Years		
Purchase Store	Please paste the store's stamp and guarantee barcode here, Please notice the purchase date should be confirmed when you buy the product		

WARRANTY

Buyers Products Company warranties all LED Strobe and LED Work Light products to the original owner against defects in workmanship and material for a period of two (2) years from the date of purchase unless otherwise specified. Buyers Products must review each warranty claim and reserves the right to offer a refund for the original sale price of the product or replace the defective light. The two (2) year warranty is non transferable, applies to the original owner, and is subject to the following terms and conditions. The warranty will be void in cases of misuse, severe abuse, and failure to properly install the LED Light. Breakage of the lens or housing, corrosion at the plug, wire wicking, voltage spikes, and product failure caused by road chemicals and acid type washes are not warrantable claims. This warranty gives you specific legal rights and you may also have other legal rights that vary from state to state.